

## 1000 MAXTRAK

The high performance Powerscreen® 1000 Maxtrak is a small to medium sized cone crusher which has been designed for direct feed applications without pre-screening on clean rock. At its heart is the Automax® cone crusher which provides excellent reduction and product cubicity for the production of high quality aggregate and subbase material. Hydraulic release capabilities are designed so that any uncrushable material entering the chamber is safely discharged.



## APPLICATIONS

#### AGGREGATE

Sand & Gravel Blasted rock River rock

#### RECYCLING



C & D waste Foundry waste

#### MINING



Processed ores Processed minerals



# TECHNICAL HIGHLIGHTS ©



#### **INCREASED PRODUCTIVITY**

- Unique crushing action provides excellent capacity, high reduction & solid product cubicity for the production of high quality aggregate & sub-base materials.
- Renowned Automax® cone crusher technology
- Economical to operate with a highly fuelefficient direct drive system



#### **SERVICEABILITY**

 Excellent access features for serviceability eg. hydraulic cabinet at ground level; unrestricted access to both sides of power unit; steel pipes in key locations.



#### VERSATILITY

- Designed for direct feed applications without pre-screening on clean rock
- Tried, tested and proven all over the world







**HOPPER** 

Wear resistant feed hopper Length: 3.38m (11') Width: 2.5m (8'2") Capacity: 4.4m3 (5.8yds3)

FEED CONVEYOR

Width: 1000mm (40") Over and under belt metal detector

**CRUSHER** 

Automax® cone crusher with all roller bearing design Min CSS: 18mm (0.7")\* Max CSS: 36mm (1.4")\*

PRODUCT CONVEYOR

Width: 800mm (32") Discharge height: 3.25m (10'8")

**POWER UNIT** 

Tier 3 Equivalent: CAT C9.3 250kW Tier 4F / Stage V: Scania DC9 257 kW (350hp) Fuel Tank Capacity: 650 L (171 US Gal)

6 TRACKS

Width: 400mm (15.7")

### **DIMENSIONS**



14.6m (47'11")



#### Transport

Length: 14.6m (47' 11") Width: 2.8m (9' 2'') Height: 3.45m (11' 4")

#### Weight

30,440kg (67,109lbs)

#### **GET IN TOUCH**

#### Dungannon

200 Coalisland Road, Dungannon, Co Tyrone, BT71 4DR, Northern Ireland Tel: +44 (0) 28 87 718 500 Fax: +44 (0) 28 87 747 231

#### Louisville

11001 Electron Drive, Louisville, Kentucky, 40299 USA Tel: +1 502 736 5200 Fax: +1 502 736 5202



The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the se of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.